

Semi Automatic L-Bar Shrink Wrapper



Features:

- * AlChrome Alloy Sealing Wire
- * Impulse Seal System
- * Magnetic Hold Down Sealing Operation
- * Adjustable Pin Perf Air Evacuation
- * Automatic Cycle Timing
- * Heavy Duty Removable Stand
- * Locking Casters

Specifications:

Machine Size:	70"L x 32"W x 39"H
Package Size:	L - .5" / 19.5" W - 4" / 15.5" H - .125" / 9"
Sealing Bar:	20"L x 17"W
Power Requirements:	220V / 1PH / 8A

414-355-7747 . **800-843-5667** . 414-355-7559 fax

Shrink Tunnel



Features:

- * PID Temperature Control
- * Teflon Mesh Rollers on Conveyor
- * Variable Speed Live Roller Conveyor
- * Heat Guards for Operator Protection
- * High Efficiency Heating Elements
- * Convection Style Heating System
- * Adjustable Blower Velocity Control

Specifications:

Machine Size:	47"L x 26"W x 51"H
Package Size:	W - (Max. 14.5") H - (Max. 9")
Camber Size:	39"L x 16"W x 9"H
Max. Conveyor Speed:	98 FPM
Power Requirements:	220V / 3PH / 28A

414-355-7747 . **800-843-5667** . 414-355-7559 fax